



Cable temperature probe glass fibre -50°C to +400°C

Application

Cable temperature probes serve to record the temperatures of fluid and gaseous media.

Technical specifications

Type KF GLS

| | |
|----------------------------|---|
| Sensor element: | Pt100 (TK3850), Pt500 (TK3850), Pt1000 (TK3850) Ni1000 (TK5000), Ni1000 (TK6180) |
| Sensor accuracy | Pt: DIN Class AA, DIN EN 60751 DIN Class A, DIN EN 60751 DIN Class B, DIN EN 60751 DIN Class C, DIN EN 60751 Ni: Class B, DIN EN 43760 (formerly) Class A, DIN EN 43760 (formerly) |
| Probe area of application: | -50°C to +400°C |
| Connections: | 2-wire, 3-wire, 4-wire |
| Measuring current: | 100Ω → 1mA; 500 Ω → 0.5mA; 1000Ω → 0.3mA |
| Connection cable: | Glass fibre, cross section 0.22mm ² |
| Cable diameter: | 4mm |
| Cable length: | Depending on customer specifications |
| Housing: | Stainless steel sleeve V4A, 6 x 50 mm (other optional sleeve lengths) |
| Protection class: | Only for dry applications |
| Areas of application: | Building technology, ventilation technology, heating technology, process technology |
| Options: | Measuring transducer of 4–20 mA or 0–10 V, variable cable lengths, connectors, other probe dimensions |

